

COLOR DOME CAMERA DCC-500PV



580TVL, 3D-DNR
DWDR, Day & Night, DSS

FEATURES

- 410K Pixel Sony 1/3" CCD
- High Resolution of 580 TV Lines
- Low up to 0.00001 Lux, Day & Night
- Digital WDR, Privacy Masking Zone, Motion Detection Function
- 3D-DNR (Digital Noise Reduction), Digital Zoom(32x)
- Built-in OSD (On Screen Display) Menu, Multi Language support
- Built-in 4~9mm Auto Iris Lens
- Option Lens (2.8~10mm, 2.8~12mm)

SPECIFICATIONS

MODEL	DCC-500PV	
Signal system	NTSC	PAL
Image Sensor	1/3" Sony Super HAD CCD	
Total Pixels	811(H) × 508(V)	795(H) × 596(V)
Effective Pixels	768(H) × 494(V)	752(H) × 582(V)
Resolution	580 TV lines (B/W : 700 TV lines with ICR)	
Scanning Frequency	15,734KHz(H), 60(V)	15,625KHz(H), 50(V)
Shutter Speed	1/60~1/100,000 sec / FLK	1/50~1/100,000 sec / FLK
Minimum illumination	Color : 0.1 Lux@F1.2 0.00001Lux (Sense-up 256x)	
Day & Night	Color / Auto / EXT / B/W True Day & Night with ICR (Option)	
Digital WDR	On / Off	
White Balance	ATW / AWB / AWC-Set / Manual / Indoor / Outdoor	
BLC	BLC / HSBLK	
AGC	Low / Middle / High / Off	
3D-DNR	On / Off	
Privacy Zone	8 Programmable Zone	
Motion Detection	4 Programmable Zone	
Sharpness	Level : 0 ~ 31	
Camera Title	On / Off	
S/N Ratio	More than 52dB	
Video Output	Composite video output 75 ohm terminated	
Lens	4~9mm DC Auto Iris Lens	
Sync. System	Internal	
Operating Humidity	30% ~ 90% RH	
Operating Temp.	-10°C to 50°	
Dimension	Ø100(Bubble) × 103.6(H)mm	
Weight	About 560g	
Power Consumption	200mA	
Power Supply	DC 12V(10.2V~14.5V) Dual Voltage(Optional) : AC24V / DC12V	

DIMENSIONS

