

# Mini Dome Camera

## Features

- Sony Super HAD II high sensitivity CCD sensor
- Sharp high sensitivity CCD sensor for 540TVL camera
- Built-in Board Lens
- 3-Axis Mechanism for free lens rotation
- DC voltage
- Vandal proof (for RYK-2Jxx)




RYK-23xx




RYK-2Jxx (Vandal Proof)

## Compact Size



RYK-23xx



RYK-2Jxx (Vandal Proof)



Model No.	RYK-2311	RYK-2383	RYK-2379
	RYK-2J49	RYK-2J83	RYK-2J79
Image Device	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II	1/3" Color Sharp
Picture Elements	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582	
Resolution	420 TVL	550 TVL	540 TVL
Min. Illumination	0.01 Lux / F1.2	0.02 Lux / F1.2	0.02 Lux / F1.2
S/N Ratio	More than 48dB		
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000		
Gamma	0.45		
Lens Furnished	Board Lens 3.6mm / F2.0 (option:2.5/4.3/6/12)		
White Balance	Auto		
Gain Control	Auto		
Sync. System	Internal		
Video Output	1 Vp-p / 75 Ohms		
Power Supply	DC12V±10%		
Power Consumption	117mA max.	140mA max.	75mA max.
Operating Temp.	-10°C ~ 50°C		